

Redefining the Agriculture



Rotavator **SUPER MAX**

-  Durable structure with a sturdy design
-  Increased productivity and ensures time savings
-  Ideal for all soil types and ensuring smooth operations
-  Reduced fuel consumption with lower maintenance costs
-  Adjustable Heavy Duty Rear Board Dampers with springs



www.apogeeagrotech.com



Rotavator SUPER MAX	5.0ft SLRT-150	5.5ft SLRT-165	6.0 ft SLRT-180	7.0 ft SLRT-201
Overall Length "L" (cm)	96	96	96	96
Overall Width "W" (cm)	178	193	208	238
Overall Height "H" (cm)	109.5	109.5	109.5	109.5
Tilling Width (cm)	150	165	180	201
Tractor Power - HP	35-45	35-45	45-55	45-55
Number of Blades	36	39/42	42	48/54/60
Three Point Hitch	Cat-II	Cat-II	Cat-II	Cat-II
Crown - Pinion (Gearbox)	13 X 23	13 X 23	13 X 23	13 X 23
Weight (kg.)	445	463-476	490	515-536
Transmission Type	Gear	Gear	Gear	Gear
Max. Working Depth (inch)	5"-8"	5"-8"	5"-8"	5"-8"

INPUT RPM	GEAR SPEED	GEAR SPUR 1	GEAR SPUR 2	GEAR SPUR 3
540	Single Speed	218	218	218
540	Multi Speed	16	19	184
540	*Multi Speed	17	18	206
540	Multi Speed	14	21	145
540	Multi Speed	15	20	164
1000	Multi Speed	13	22	239

APOGEE AGROTECH PVT LTDwww.apogeeleveller.com

7624002265

www.apogeeagrotech.comSales@apogeeagrotech.com

540, Near Reliance Petrol Pump, Garh Road, Hapur, UP, 245101